



PowerGem Plus

51.2V/14.3kWh/8000cycles

FEATURES

0.5C
Continuous Power

10
Year Warranty

32
Units Stackable

Neat
Wall mount

Handy
Free Monitor

8000
Cycles

- Ultra safe LFP material
- Short circuit protection
- Flexible remote upgrade
- Wide range inverter compatibility
- Multi protection to avoid over discharge
- Smart BMS management for longer lifespan
- Active balancing charging, low self consumption



BITEK SOLAR PRIVATE LIMITED

+91 743953876

INFO@BITEKENERGY.COM

WWW.BITEKENERGY.COM

PLOT 3211/FF, BLOCK 14, GODOWN AREA, BHABAT, ZIRAKPUR, PUNJAB INDIA 140603



Module Name

PowerGem Plus

Cell Type	LFP
Rated Power	14.3kWh
Rated Capacity	280Ah
Rated Voltage	51.2V
Charge Voltage (Vdc)	56.5
Battery Charge Current(A)	140(max continuous) 150 (start limit current to 10A, retest every 10 minutes) 160 (peak1 15S) 180 (peak2 500ms)
Battery Discharge Current(A)	140(max continuous) 150(start giving over-current alarm but not stop discharging) 160 (peak1 5minutes) 200 (peak2 500ms)
Parallel	Up to 32 units parallelable w/o extra device needed, slave battery drops offline or come back alive does not affect system running
IP Level	IP20
Dimension(W*D*H,mm)	900*475*238mm
Weigh	115Kg
Communicationt	CAN/RS485
Robust Applications	Auto-addressing and stronger protection
DOD	90%
Cycles	8000
Compatible Inverter	Victron, Luxpower, Deye, Voltronic, SMA Goodwe, Growatt, Sofar, Solark, SRNE, Must
Humidity	5%~85% RH (No condensation)
Work Temperature	-20 °C ~ +55 °C
Storage Temperature	-10 °C ~ +35 °C
Remote Maintenance	Flexible remote upgrade, Original firmware backup to prevent upgrade failure
Warranty *	10 year, 8000 cycles
Certification	CE UN38.3 IEC62619
Protection	Over charge/discharge/current/voltage/temperature protection Short circuit protection, Reverse connection protection Charge balance, Low SOC protection