



8  
Series per stack

20  
Stack parallel

10  
Year warranty

# POWER STACK

## HIGH VOLTAGE

BETTER EFFICIENCY

## FEATURES

- 10 year warranty
- Ultra safe LFP material
- Short circuit protection
- Flexible remote upgrade
- Wide range inverter compatibility

### BITEK SOLAR PRIVATE LIMITED

+91 743953876

INFO@BITEKENERGY.COM

WWW.BITEKENERGY.COM

PLOT 3211/FF, BLOCK 14, GODOWN AREA, BHABAT,  
ZIRAKPUR, PUNJAB INDIA 140603



# POWER STACK

Model	PowerStack
Scalable Connection	2~8pcs series per stack, up to 20 stack parallel
Battery stack nominal energy	10kWh 15kWh 20kWh 25kWh 30kWh 35kWh 40kWh
Dimension	736*382*577mm/735mm/893mm/1051mm/1209mm/1367mm/1525mm
Weight	110Kg/155Kg/200Kg/245Kg/290Kg/335Kg/380Kg
Battery module nominal voltage	70.4V
Battery module nominal capacity	72Ah
Battery module nominal energy	5.069kWh
Protection	IP65
Battery module voltage range	61.6V~80.3V
Recommend charge/discharge current	36A, 0.5C per battery module
Max continuous charge/discharge current	50.4A, 0.7C per battery module
Max continuous charge/discharge power	3.548KW per battery module
Max. series number per cluster	8 series
Cluster parallel	Up to 20 clusters, without extra unit needed
Charging/Discharging temperature	0 °C ~ +55 °C , -20 °C ~ +55 °C
Recommend storage temperature	-10 °C ~ +35 °C (Max range -30 °C ~ +55 °C)
Recommend storage humidity	10% RH~90% RH
Warranty *	10 year, 6000 cycles
Certification	CE UN38.3 IEC62619
Remote Maintenance	Flexible remote upgrade, Original firmware backup to prevent upgrade failure

\* @ 25 °C, 90% Dod, 0.5C testing condition